

Galvanized **Steel Rigid Metal Conduit**



Wheatland *Tube*

JMC STEEL GROUP

RMC: The Ultimate Protection

Wheatland's listed steel RMC has the thickest wall of all the metallic raceways and is recognized by the industry as providing the most physical protection for conductors and cables. Steel conduit doesn't burn, contribute to smoke volume, emit potentially escape-inhibiting fire gases, or add to fuel load or flame spread. It also provides an excellent electrical path to ground and is recognized as an equipment grounding conductor by NFPA 70: National Electrical Code® 250.118 (2). Steel conduit was introduced in the early 1900's as a raceway system and is still the Ultimate Protection for cable and conductors today.

The Winning Team

When the job needs to be done on time and within budget, rely on Wheatland, the largest producer of RMC in the country. Our in-house, hot-dip galvanizing process is the quality benchmark for the industry. Wheatland's RMC is rolled and galvanized, inside and out, using the latest technology. And only Wheatland produces couplings in the same mills as its rigid metal conduit. Experience. Quality. Total in-house capabilities. You and Wheatland. That's *the* winning team.

A Quick Look at Wheatland's Steel RMC

Steel Rigid Metal Conduit is manufactured from mild steel tube. It has an accurate circular cross section, a uniform wall thickness, a defect free interior surface, and a continuous welded seam.

Applications: Wheatland Galvanized Steel RMC can be installed indoors or outdoors, in dry or wet locations, exposed or concealed, in all kinds of atmospheric conditions, and in hazardous locations, when installed in accordance with National Electrical Code® (NEC®).

Coatings: The interior and exterior surfaces are thoroughly and evenly coated with zinc using the hot-dip galvanizing process, so that metal-to-metal contact and galvanic protection against corrosion are provided. A clear post-galvanizing coating provides further protection against corrosion, and a lubricating coating is applied to the interior surface to reduce friction during wire insertion.

Sizes: Nominal trade sizes are from ½" to 6"

Lengths: RMC is produced in traditional standard lengths of 10 feet, including the coupling. It is threaded on both ends,



with a coupling applied to one end and a thread protector, industry color-coded by size, to the other. Wheatland recently introduced 20 ft. lengths; they are available in trade sizes 2" through 6".

Protection: RMC offers long-lasting value: provides exceptional physical protection, reduces exposure to EMF, shields against Electro-Magnetic Interference (EMI) and provides an excellent electrical path to ground.

Green: The steel used to produce Wheatland's RMC contains recycled steel and is virtually totally recyclable. Steel is the most recycled material in the world, but the recycling may not take place for decades, since the service life of steel conduit is very long. Conductors can easily be removed and new conductors inserted; additional circuits may be added in the same conduit.

Specifications

Wheatland's Galvanized steel Rigid Metal Conduit (RMC) is manufactured in accordance with the latest specifications and standards of ANSI® C80.1, UL-6, and federal specification WW-C-581. The pitch of RMC threads conforms to the American National Standard for Pipe Threads, General Purpose (Inch), ANSI/ASME B1.20.1. The taper of threads is 3/4 inch per foot (1 in 16).

Thread Protectors

Wheatland's RMC is threaded on both ends, with a coupling applied to one end and a thread protector, industry color-coded by size, to the other.

Black: ½", 1 ½", 2 ½", and 3 ½"

Red: ¾", 1 ¼"

Blue: 1", 2", 3", 4", 5" and 6"

Protects Against EMF/EMI

Steel RMC reduces exposure to EMF and shields against Electro-Magnetic Interference (EMI) at power frequencies which could impact computers and other sensitive electronic equipment and controls. Contact Wheatland's Marketing Department at info@wheatland.com for a copy of Georgia Tech's

Grounding and Electro-Magnetic Interference (GEMI) Analysis software.

Provides Equipment Grounding

Steel RMC is approved for use by the NEC® as an equipment grounding conductor with its associated couplings and appropriate fittings.

Hot-Dip Galvanized Rigid Metal Conduit - Steel

Weights and Dimensions

Trade Size	Metric Designator	Threads Per Inch	Acceptable Length of Finished Conduit without Coupling			Weight 10 Unit Lengths with Couplings		Nominal Outside Diameter*		Nominal Inside Diameter*		Nominal Wall Thickness*	
			ft.	(+/- 1/4 in.) in.	(+/- 6 mm) mm	lb	kg	in.	mm	in.	mm	in.	mm
½	16	14	9	11¼	3030	82	37.20	0.840	21.34	0.632	16.05	.104	2.64
¾	21	14	9	11¼	3030	109	49.44	1.050	26.67	0.836	21.23	.107	2.72
1	27	11½	9	11	3025	161	37.03	1.315	33.40	1.063	27.00	.126	3.20
1¼	35	11½	9	11	3025	218	98.88	1.660	42.16	1.394	35.41	.133	3.38
1½	41	11½	9	11	3025	263	119.30	1.900	48.26	1.624	41.25	.138	3.51
2	53	11½	9	11	3025	350	158.76	2.375	60.33	2.083	52.91	.146	3.71
2½	63	8	9	10½	3010	559	253.56	2.875	73.03	2.489	63.22	.193	4.90
3	78	8	9	10½	3010	727	329.77	3.500	88.90	3.090	78.49	.205	5.21
3½	91	8	9	10¼	3005	880	399.17	4.000	101.60	3.570	90.68	.215	5.46
4	103	8	9	10¼	3005	1030	467.21	4.500	114.30	4.050	102.87	.225	5.72
5	129	8	9	10	2995	1400	635.04	5.563	141.30	5.073	128.85	.245	6.22
6	155	8	9	10	2995	1840	834.62	6.625	168.28	6.093	154.76	.266	6.76

*For information only, not a UL 6 requirement.

Rigid Steel Conduit is manufactured to the lengths shown above, so when a straight-tapped coupling Wheatland trade sizes 3 through 6 are UL Listed for use with directional boring equipment.

Packaging

Trade Size	Metric Designator	Threads Protectors Color	Quantity Per Bundle		Quantity Per Lift				Weight Per Lift		Volume Per Lift	
			Feet	Meters	Pieces	Bundles	Feet	Meters	Pounds	Kilograms	Cu. Feet	Cu. m
½	16	Black	100	30.5	---	25	2,500	762	2050	929.9	19.4	0.6
¾	21	Red	50	15.2	---	40	2,000	610	2180	988.8	26.7	0.8
1	27	Blue	50	15.2	---	25	1,250	381	2013	912.9	22.2	0.6
1¼	35	Red	---	---	90	---	900	274	1962	890.0	28.3	0.8
1½	41	Black	---	---	80	---	800	244	2104	954.4	27.2	0.8
2	53	Blue	---	---	60	---	600	183	2100	952.6	36.1	1.0
2½	63	Black	---	---	37	---	370	113	2068	938.2	35.0	1.0
3	78	Blue	---	---	30	---	300	91	2181	989.3	41.5	1.2
3½	91	Black	---	---	25	---	250	76	2200	997.9	43.3	1.2
4	103	Blue	---	---	20	---	200	61	2060	934.4	48.6	1.4
5	129	Blue	---	---	15	---	150	46	2100	952.6	52.1	1.5
6	155	Blue	---	---	10	---	100	30	1840	834.6	43.8	1.2

The quantity per Lift conforms to the National Electrical Manufacturers Association Standards Publication RN-2 Packaging of Master Bundles for Steel Rigid Conduit, Intermediate Metal Conduit (IMC), and Electrical Metallic Tubing.



JMC Steel Group
Pipe and Tube Solutions

Corporate Office

3201 Enterprise Pkwy., Ste. 150,
Beechwood, OH 44122-7329
Ph: (216) 910-3700



Wheatland Tube
JMC STEEL GROUP

Wheatland Tube

700 South Dock Street,
Sharon, PA 16146
Ph: (800) 257-8182
Fax: (724) 346-7260
info@wheatland.com

Wheatland produces a full line of listed electrical conduit, EMT and tubular fittings. We supply Steel and Aluminum Rigid Metal Conduit (RMC), Steel Intermediate Metal Conduit (IMC) and Steel Electrical Metallic Tubing (EMT). We also manufacture a full line of complementary tubular fittings made from the same materials as our raceways — nipples, elbows, couplings and running thread. (See Wheatland's individual product literature for specific product details.)

All Wheatland manufacturing locations' quality management systems are certified to ISO 9001:2008 requirements.

For more information contact Wheatland's Electrical Sales Department at 800-257-8182, email: info@wheatland.com or visit our website at www.wheatland.com.



Made in U.S.A.